

|                      | DHC-3       | DHC-5       | DHS-10      | DHS-15      | DHS-20      |
|----------------------|-------------|-------------|-------------|-------------|-------------|
| Tonnage              | 3.3         | 5.5         | 11          | 16.5        | 22          |
| Stroke (inches)      | 5.9"        | 5.9"        | 5.9"        | 5.9"        | 5.9"        |
| Open Height (inches) | 9.8"        | 9.8"        | 13.8"       | 13.8"       | 13.8"       |
| Approach Speed (IPM) | 368         | 315         | 500         | 500         | 437         |
| Pressing Speed (IPM) | 153         | 97          | 63          | 47          | 44          |
| Retract Speed (IPM)  | 263         | 140         | 290         | 259         | 259         |
| Bed Table (WxD)      | 17.7"x14.2" | 17.7"x14.2" | 23.6"x14.2" | 23.6"x14.2" | 27.6"x15.7" |
| Power                | 230V/3Ph    | 230V/3Ph    | 230V/3Ph    | 230V/3Ph    | 230V/3Ph    |
| Motor Speed (HP)     | 2           | 2           | 3           | 3           | 5           |
| Weight (lbs.)        | 775         | 795         | 2,094       | 2,755       | 3,527       |
| Shank Hole Diameter  | 1.18"       | 1.18"       | 1.18"       | 1.18"       | 1.18"       |
| Throat Distance      | 6.3"        | 6.3"        | 7.1"        | 8.1"        | 8.7"        |
| Frame Material       | Cast Iron   | Cast Iron   | Steel       | Steel       | Steel       |



### Features:

- Steel or cast iron frame construction available based on tonnage
- Shank holder with dual screw adjustment
- Standard pressure and speed control
- Allen Bradley PLC Control System with Operator Interface
- 1 year warranty on material and workmanship
- Compact heavy duty design built for reliability
- Energy efficient system
- Low noise output for quiet operation

### Options:

- Complete Integration Solutions
- Complete Automation Solutions
- Light Curtain Guarding
- Bolt on Expanded Metal Guarding
- Machining Requirements
- Work Table with Casters
- Multiple Control Platforms
- 460V/3PH Power System
- Pressure Switch
- Air/Water Cooler
- Reservoir Heater
- Increased Tonnage (+40 tons)
- Other options available upon request

*Other options available upon request*