

	DHS-5R	DHS-10R	DHS-20R	DHS-40R	DHS-50R
Tonnage	5.5	11	22	44	55
Stroke	5.9"	7.9"	7.9"	7.9"	7.9"
Open Height	13.8"	13.8"	13.8"	13.8"	13.8"
Approach Speed (IPM)	915	718	515	300	300
Pressing Speed (IPM)	113	66	35	28	28
Retract Speed (IPM)	940	852	522	280	260
Bed Table (W"xD")	17.7"x13.8"	18.9"x15.7"	19.7"x17.3"	23.6"x15.7"	23.6"x19.7"
Ram Dim. (WxD)	11.8"x7.9"	12.2"x5.9"	15.7"x9.8"	19.7"x9.8"	20.5"x15.7"
Motor Speed (HP)	3	3	5	7.5	7.5
Weight	1,870 lbs	2,881 lbs	3,891 lbs	4,850 lbs	5,732 lbs
Power	230V/3Ph	230V/3Ph	230V/3Ph	230V/3Ph	230V/3Ph
Throat Distance	7.3"	8"	8.7"	8.7"	10.6"



Features:

- Guided ram bolster
- Adjustable up & slow down limit switches
- Variable pressing speed
- Mechanical adjustment for bottom stop
- Speeds up to 940 IPM
- Steel frame construction
- 1 year warranty on material and workmanship
- Allen Bradley PLC Control System with Operator Interface
- Compact heavy duty design built for reliability
- Energy efficient system
- Low noise output for quiet operation

Options:

- Complete Integration Solutions
- Complete Automation Solutions
- Light Curtain Guarding
- Bolt on Expanded Metal Guarding
- Machining Requirements
- Work Table with Casters
- Multiple Control Platforms
- 460V/3PH Power System
- Pressure Switch
- Air/Water Cooler
- Reservoir Heater
- Increased Tonnage (+40 tons)

Other options available upon request