

570 Ton 4-Post Hot Forming/SPF Press

Tonnage:	570
Application:	Hot Forming/SPF
Industry:	Aerospace
Frame Style:	4-Post
Special Features:	<ul style="list-style-type: none"> • Bed Shuttle System • Ejector System • Insulated automatic doors • Active Leveling Control



Custom Features:

- Used for hot forming and superplastic forming of titanium for the aerospace industry
- (4) 8" diameter chrome housing posts with graphite impregnated bronze bushings for superior ram guidance and rigidity
- 82" x 112" bed shuttle system
- Insulated automatic door system grants 4 sided access while maximizing heat efficiency
- Equipped with two (2) sets of press ejectors to lift molds off of the bed platen
- Equipped with four-axis Active Leveling Control (ALC) for precision bed to ram parallelism
- Kidney loop filter/cooler circuit with thermostatically-controlled water-oil heat exchanger
- Calculated Ram Speeds: Fast Approach: 0-70 IPM; Pressing: 1/8-15 IPM; Slow Retract/Stripping: 1-55 IPM; Return: 55 IPM

Common Features on Beckwood Presses:

- Heavy duty box beam design for superior rigidity and modular tie rod assembly utilizing pre-tensioning nuts for optimum performance
- Fully adjustable Parker cylinders with full rated tonnage throughout the stroke
- PressLink Remote Support module for complementary diagnostics & troubleshooting
- Dual linear and pressure transducers in the main ram cylinders for optimal reliability and redundancy
- Allen Bradley or Siemens PLC, programmable control system with touch screen HMI and Recipe Functionality
- Structure designed for Infinite Life in accordance with rigorous simulation analysis through FEA (Finite Element Analysis) design testing
- Backed by Beckwood's industry leading dedicated service and support team



889 Horan Drive
 St. Louis, MO 63026 - USA
 800.737.0111
 beckwoodpress.com
 sales@beckwoodpress.com

Learn more about our
 4-Post presses

Learn more about Hot Forming/SPF